

LED 12 V (DC)



Entrata/ <i>Input</i> 95-260 Vac / 50-60 Hz	Uscita/ <i>Output</i> 12 V (DC), 12 W	Dimensioni/ <i>Dimensions</i> 120x32x22 mm
Thermal protection	Protezione di corto circuito/ <i>Short circuit protection</i>	
550-041-50 550-016-50		550-016-50



Entrata/ <i>Input</i> 230 V	Frequenza/ <i>Frequenz</i> 50-60 Hz	Uscita/ <i>Output</i> 12 V (DC), 12 W
Dimensioni/ <i>Dimensions</i> 103x67x30 mm	Dimmbar 10kOhm	Dimmable 10kOhm
550-049-50		



Entrata/ <i>Input</i> 230 V	Frequenza/ <i>Frequenz</i> 50-60 Hz	Uscita/ <i>Output</i> 12 V(DC) 4,2 W
Dimensioni/ <i>Dimensions</i> 46x34x24 mm	Protezione di sovraccarico <i>Overload protection</i>	Protezione di corto circuito <i>Short circuit protection</i>
Lunghezza cavo/ <i>Cable length</i> : 2000 mm		
550-052-51		



Entrata/ <i>Input</i> 230 V	Frequenza/ <i>Frequenz</i> 50-60 Hz	Uscita/ <i>Output</i> 12 V(DC) 10 W
Dimensioni/ <i>Dimensions</i> 60x44x27 mm	Protezione di sovraccarico <i>Overload protection</i>	Protezione di corto circuito <i>Short circuit protection</i>
Lunghezza cavo/ <i>Cable length</i> : 2000 mm		
550-053-51		